
Various Virtual-Reactor Challenges

Marvin L. Adams
Texas A&M University
mladams@tamu.edu


SLC workshop, Feb 23-24, 2006

There's a lot to address in addition to numerics and MPI.




- Disclaimer: I wrote this talk between 1:30 and 3:30 yesterday, and I haven't slept much this week.
 - ⇒ Let's begin with low expectations.
 - ⇒ Apologies to the materials group. I worked while you talked.
 - \Rightarrow It's all Abder's fault.
- Virtual Reactor requires a large multi-disciplinary team.
 - \Rightarrow It is difficult to build an effective team. It takes a while.
 - \Rightarrow It is really difficult to build an effective multi-disciplinary team.
 - ⇒ It is really really difficult to build an effective multi-disciplinary team that is geographically dispersed.
 - \Rightarrow Difficulty scales much worse than linear in N_{people} or $N_{disciplines}$.
 - ⇒ Face-to-face meetings are essential, in my opinion. Video conferences can augment but not replace them.
 - ⇒ People-time for communication is essential and must be in the budget.

There's a lot to address in addition to numerics and MPI.



- Virtual Reactor requires coupled-physics code.
 - ⇒ Can't just stitch together codes for the different physical phenomena.
 - ⇒ In the tera- and peta- worlds, can't just stitch together "packages" or "modules" written independently for the different phenomena
 - Can't copy data from one set of parallel data containers to another
 - Can't stand first-order time discretizations (like simplest operator splitting)
 - May sometimes want to implicitly solve coupled sub-operators
 - ⇒ A phenomenon coupled to others may need different numerical methods (compared to un-coupled case).
- Virtual Reactor requires V&V of coupled-physics code.
 - ⇒ Incredibly important in nuclear applications.
 - ⇒ V&V of each phenomenon's simulation is essential but very insufficient.
 - ⇒ Coupled-physics analytic solutions (for verification) are difficult.
 - ⇒ Coupled-physics experiments (validation) are difficult and expensive.
 - ⇒ Uncertainty and error estimates are essential (and difficult).

There's a lot to address in addition to numerics and MPI.



- It's a long way from dozens to thousands of processors.
 - ⇒ Today's state-of-art reactor-analysis codes are not close to this.
 - ⇒ Some research codes and general-purpose transport codes are.
- It's even farther from 1,000 to 100,000.
 - ⇒ Let's not underestimate this!
 - ⇒ It looks like petascale will require 100's of thousands of threads running simultaneously. This is where the hardware is heading.
 - ⇒ Transport solution methods today do not scale to this level.
 - Sweeps don't.
 - Block-Jacobi takes more iterations as blocks shrink.
 - We're working on it! ☺

One technical point (sorry – couldn't resist): full coupling.


- Particle transport phase-space is 6-dimensional (3 position, 2 direction, 1 energy) plus time.
 - \Rightarrow Medium resolution in direction and energy P 10⁴-10⁵ unknowns per spatial point.
- In a steady-state or eigenvalue problem:

The solution at each point in phase space influences the solution at every other point in phase space!


- ⇒ Thus, no matter how you decompose the problem, each processor must communicate with every other processor (perhaps indirectly).
- ⇒ If a transport person collaborates with others on a parallel code, it is very important to convey this point at the beginning!
- In a time-dependent problem:

The solution at each point in phase space at a given time influences the solution at every other point in phase space at some later time.


Okay, one more technical point regarding transport ...



- When you add resolution in one phase-space variable (for example, resolving true spatial geometry), you complicate the solution in other variables.
- Example: explicit fuel pins instead of homogenized pin cells.



Where we are at Texas A&M



- At Texas A&M, we have been collaborating closely with math and comp-sci. Team includes:
 - ⇒ Nuclear Engrg: Marvin Adams, Jim Morel
 - ⇒ Comp-Sci: Nancy Amato, Lawrence Rauchwerger, Bjarne Stroustrup
 - ⇒ Math: Raytcho Lazarov, with others coming on board
- We have a parallel transport code (PDT). Today it is:
 - ⇒ 3D, multigroup, discrete ordinates
 - ⇒ Structured or unstructured (arbitrary polyhedral) grids
 - ⇒ FV and Discontinuous Galerkin spatial discretizations
 - ⇒ TSA preconditioners and Krylov iterative methods (nested)
 - ⇒ Built on solid computer-science infrastructure (STAPL)
 - ⇒ Easy to add new methods very nice transport testbed!
- We are working on:
 - ⇒ A library to support transport calculations
 - ⇒ A multi-physics library / infrastructure
 - ⇒ A nice multi-physics algorithm testbed
- Perhaps this is part of a starting point?